

# TOSHIBA

**e-STUDIO™ 5518A**

**e-STUDIO™ 6518A**

**e-STUDIO™ 7518A**

**e-STUDIO™ 8518A**

- Black & White Multifunction Printer
- Up to 85 PPM
- Large Workgroup
- Copy, Print, Scan, Fax
- Secure MFP
- Solutions Ready



**TOGETHER  
INFORMATION**

# e-STUDIO™ 5518A/6518A/7518A/8518A

## Main Specifications

<b>Copy System</b>	Indirect Electrostatic Photographic Method/OPC/Laser Printing/ Heat Roller Fusing
<b>Display</b>	10.1" Colour WSVGA Touch Screen Tilting Display
<b>Copy Speed</b>	55/65/75/85 PPM (LT)
<b>First Copy Out</b>	5.2/5.2/4.5/4.1 Seconds
<b>Warm-Up Time</b>	Approx. 24/24/20/20 Seconds
<b>Copy Resolution</b>	2400dpi (Equivalence) x 600dpi (with Smoothing)
<b>Stack Feed Bypass</b>	3.9" x 5.8" to 13" x 19", 12" x 47" Banner, Envelope
<b>Multiple Copying</b>	Up to 9,999 Copies
<b>Paper Capacity</b>	Standard 3,520 Sheets/Max. 6,020 Sheets
<b>Original Feed</b>	Standard 300-Sheet DSDF
<b>Scan Speed &amp; Weights</b>	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour), Simplex: 9.3-110 lb Index, Duplex: 9.3-110 lb Index
<b>Max. Original Size</b>	LD
<b>Paper Feed Sizes</b>	Drawers: 540 Sheets-ST-R to 12" x 18" Integral Tandem LCF 1,160 x 2 LT-Only Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner Opt. 2,500-Sheet Ext. LCF LT-Only Tandem LCF 1,160 Sheets x 2-16 lb Bond-140 lb Index Plus 540 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 120 Sheets-16 lb Bond-110 lb Cover Opt. 2,500-Sheet Ext. LCF LT-Only -16 lb Bond-140 lb Index Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
<b>Paper Weights</b>	
<b>Duplex</b>	
<b>Reproduction Ratio</b>	25% to 400%
<b>Max Duty Cycle</b>	Max. 520K/590K/660K/720K Month
<b>Weight</b>	Approx. 430 lb
<b>Approx. Dimensions</b>	37.6" (W) x 27.5" (D) x 48.3" (H)
<b>Toner Yield</b>	106,600 @ 5%
<b>Power Source</b>	120 Volts, 50/60 Hz, 16 Amps
<b>Power Consumption</b>	Maximum 2.0kW (120V)
<b>CPU</b>	Intel Atom™ 1.33 GHz (Dual-Core)
<b>Memory</b>	4GB
<b>Hard Disk Drive</b>	320GB Self-Encrypting Drive

## e-BRIDGE Next Print Specifications

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Speed</b>	55/65/75/85 PPM (LT)
<b>Print Resolution</b>	600 x 600 dpi, 2,400 (Equivalence) x 600 dpi (With Smoothing), 1,200 x 1,200 dpi (2-bit) or 3,600 (Equivalence) x 1,200 dpi, PS Only
<b>Operating Systems</b>	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7,8.1,10, Windows Server® 2012/R2, Windows Server 2016®, Macintosh® (macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, macOS 10.12, 10.13), Unix®, Linux®
<b>Network Protocols</b>	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh® Environments
<b>Printing Protocols</b>	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or EtherTalk, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
<b>Print Drivers</b>	Windows Server® 2008 SP2 (32-bit, 64-bit) Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit,64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server 2016®, Windows® 10 (32-bit, 64-bit), macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, macOS 10.12, 10.13 RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed) Optional
<b>Interface</b>	802.11b/g/n, Wireless LAN, Optional Bluetooth
<b>Wireless Device</b>	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
<b>Device Management</b>	TopAccess
<b>Account Control</b>	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® domain) or Login Name/ Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
<b>Accessibility Features</b>	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



## Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)\* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for firmware update, Integrity Check function, Image Log, Card Authentication, NFC Authentication

## Environmental Stds. Certification

\*Conformance with HCD-PPv1.0 in High Security Mode.  
ENERGY STAR® (V2.0), EPEAT Gold  
WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint®, Mopria®

## Scan Specifications

<b>Scan Speed</b>	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour)
<b>Scan Modes</b>	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
<b>Scan Resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>File Formats</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
<b>Image Compression</b>	Colour/Grayscale: JPEG (High, Middle, Low)

## Facsimile Specifications

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 IPM

## e-Filing Specifications

<b>Operation Method</b>	Colour Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## Accessories (Options)

<b>Additional Paper Options</b>		FIPS 140-2 Validated SED	GE-1230
Large Capacity Feeder	MP-2502L-B	Embedded OCR Enabler	GS-1080
<b>Finishing Options</b>		Multi-Station Print Enabler	GS-1090
50-Sheet Staple Finisher	MJ-1111-B	Mototype Font Option	GB-2050L
Saddle-Stitch Finisher	MJ-1112-B	<b>Miscellaneous Options</b>	
Hole Punch Unit	MJ-6106N	Accessible Arm	KK-2560
Side Exit Tray	KA-6551-ET	Harness Kit for Coin Controller	GQ-1280
Finisher Guide Rail	KN-1103	<b>e-BRIDGE Plus Apps</b>	
<b>Connectivity/Security Options</b>		Office365	GB-365Node
FAX Unit/2nd Line for FAX Unit	GD-1370NA-N	Includes:	
Wireless LAN/Bluetooth	GN-4020	OneDrive® 365 App	
Bluetooth Keyboard	GR-9000	SharePoint® 365 App	
Accessory Tray	GR-1330	Exchange 365 App	
Panel 10-Key Option	GR-1340		
Card Reader Holder	GR-1320		
Meta Scan Enabler	GS-1010		
IPsec Enabler	GP-1080		
Unicode Font Enabler	GS-1007		

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership or Toshiba Tec Canada Business Solutions Inc. Branch for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

## Corporate Office

75 Tiverton Court  
Markham, Ontario  
L3R 4M8

Phone  
Fax

905-470-3500  
905-470-3450

Web Site

www.toshiba.ca