

TOSHIBA

e-STUDIO2822AF

- > Black & White MFP
- > 28 PPM
- > Small Work Group
- > Copy, Print, Scan, Fax
- > Mobile Enabled

Don't let the small size fool you. This compact Toshiba e-STUDIO2822AF combines a letter sized footprint with a ledger sized capability. You'll find all the functions you need, including copying, printing and scanning—even faxing. First copy out time is 6.5 seconds, with impressive 2,400 x 600 dpi output delivered at 28 pages per minute. The Reversing Automatic Document Feeder (RADF) and Automatic Duplex Unit (ADU) enable two-sided copying and printing that save money and resources. An Ethernet network interface ensures seamless integration, and optional wireless connectivity enables direct WIFI printing and maximize the benefits of Toshiba's e-BRIDGE Print & Capture application Mobile App.



Specifications

| | |
|--------------------------------------|---|
| Copying/Printing Process Type | Indirect Electrostatic Photographic Method Desktop |
| Original Scanning Method | Contact Image Sensor (CIS) |
| Resolution | 2400 x 600 dpi (with Smoothing) |
| Gradation | 256 Steps |
| Original Platen Type | 50-Sheet RADF (14-28 lb) |
| Available Original Size | ST-R to LD |
| Available Paper Size | Drawer: LT Only Stack Feed Bypass: ST-R, LT, LG, LD, Envelope |
| Paper Supply | Standard: Drawer (250 Sheets x 1) Stack Feed Bypass (50 Sheets) |
| Available Paper Weight | Drawer: 17-20 lb Stack Feed Bypass: 14-120 lb Inx Auto Duplexing Unit: 17-20 lb |
| Paper Exit | Face Down/Inner Tray |
| Warm-up Time | Approx. 18 Seconds (Scanner Function Available During Warm-Up) |
| Counter | Electronic Counter (Indication by LCD Display) |
| Memory | 512 MB |
| Department Codes | 100 |
| Power Supply | 115 Volts, 12 Amps |
| Power Consumption | Maximum: 1.5kW |
| Dimensions | Approx. 15.3" x 21.25" x 20" (W x D x H) |
| Weight | Approx. 62.7 lb |
| Special Features | Energy Saver, Auto Sleep Mode, Department Code |
| Max Duty Cycle | 64K Copies |
| Certifications | Energy Star V3.0, EPEAT (GOLD) + RoHS Compliant |
| Worldwide Safety Stds. | UL, GS, CE, CDRH, SASO, IRAM, EAC, CCC |
| Black Toner Yield | 17.5 K impressions based on 5% coverage |

Copy Specifications

| | |
|------------------------------|--|
| Copying Speed | 28 PPM |
| Original Scan Speed | 25 SPM (by Using RADF) |
| Scan Resolution | 600 x 600 dpi (for Copying) |
| First Copy Time | Less Than 6.5 Seconds |
| Original/Copy Size | ST-R to LD |
| Original Mode | Photo, Text/Photo, Text, Background Erase |
| Image Density Control | Automatic/Manual (9 Steps) |
| Reproduction Ratio | Zoom: 25% to 400% in 1% Increments |
| Multiple Copying | Up to 999 Copies (Ten Key Input) |
| Special Features | Department Codes (100), Interrupt, APS/AMS, Auto Job Start, Automatic Sort Mode, ID Card Copy, One Touch Key (2) |

Print Specifications (Standard)

| | |
|----------------------------|--|
| Printing Speed | 28 PPM |
| Printing Resolution | 2400 x 600 dpi (with Smoothing) |
| Interface | Standard: 10/100 Base-T, USB 2.0 Optional: IEEE802.11 b,g,n |
| PDL | PCL 6 Emulation |
| USB Direct Printing | JPEG, TIFF, PDF (Only PDF Created by MFP Can Be Printed) |
| Support OS | Windows 7, 8, 8.1, 10, 2008R2, 2012, 2012 R2, 2016, (WHQL), CUPS PCL Unix, Linux 5.10.x, 6.5.x |

Scan Specifications (Standard)

| | |
|----------------------------|---|
| Connection Type | Standard: 10/100 Base-T Optional: IEEE802.11 b,g,n |
| Scanning Resolution | 100/150/200/300/400/600 dpi |
| Scanning Speed | 25 SPM (BW) at 600 dpi, 24 SPM (Colour) @ 200 dpi, 18 SPM @ 300 dpi |
| Scan Agent | Scan to File, SMB, FTP, Scan to Email, Scan to USB, TWIN IOS & Android Support Via e-BRIDGE Print & Capture App (Free on iStore or Play) |

Paper Handling

Reversing Automatic Document Feeder (RADF)

| | |
|------------------------------|------------|
| Stack Capacity | 50 Sheets |
| Original Setting | Face Up |
| Original Paper Size | ST-R to LD |
| Original Paper Weight | 14-28 lb |

FAX Specifications

| | |
|------------------------------------|--|
| Compatibility | Super G3, G3 |
| Image Format on PSTN | JBIG, MMR, MR, MH |
| Document Size | ST-R-LD |
| Modem Speed | 33.6 kbps to 2.4 kbps (Automatic Fallback) |
| Transmission Speed | Approx. 3 Seconds |
| Communication Protocols | ITU-T T.30 |
| Memory Transmission | Max 256 Jobs, 220 Destinations/Job, 384 Pages/File |
| Options | |
| Cabinet | ST-2505F |
| Wireless LAN Module | GN-1160 |
| Harness for Coin Controller | GQ-1131 |



Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership or Toshiba Tec Canada Business Solutions Inc. Branch for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

75 Tiverton Court
Markham, Ontario
L3R 4M8

Phone
Fax

905-470-3500
905-470-3450

Web Site

www.toshibatec.ca