TOSHIBA





For flat-head printers

AW5 is a new generation quality product designed to meet today's varied and demanding printing standards. This improved resin enhanced wax quality offers superior mechanical and smudge resistance. It has been specifically developed for the new generation of Toshiba flat-head printers. Providing very good, clear printed images of text and barcodes onto a wide range of labels stocks, from uncoated to high gloss papers and synthetics, it offers a blackness above 2.0 ODR and heat resistance up to 100°C.

As with all Toshiba ribbon products, AW5 offers the best in printhead protection with its superior back coating.

Toshiba AW5 ribbons – new generation wax ribbon for demanding applications.

Characteristics						
Excellent multi-receptor compatibility	Excellent print quality					
Very high smudge and scratch resistance						
Specifications (Performances expressed in this sheet are for the black ribbon)						

Specifications (Performances expressed in this sheet are for the black ribbon)						
Ink	Туре	Wax				
	Melting point	65°C (149°F)				
Carrier	Film thickness	<9 µm				
	PET thickness	4.5 µm				
	Tensile strenght	>220 N/mm² (MD)				
Back Coating	Silicone product based	Friction coefficient Kd < 0.2				
Colours	Black					

Ribbon is anti static build up treated. Storage: 12 months, 5-35°C (40-95°F), 20-80% Humidity

Certifications and Approvals (For other standards, please contact us)						
Food Contact	1935/2004/EC					
Heavy metals	EC 98/638.					
TSCA	The ribbon does not contain any of the toxic substances mentioned in this list.					
RoHs/WEEE	EC directives 2002/65 and 2002/96. The compliance to the limitation of dangerous substances in electrical equipment.					
EC Directives	1999/45/EC. The ribbon does not contain any substance classified as dangerous for health.					

Always Choose Toshiba Ribbons for Toshiba Printers

The wide range of Toshiba ribbons available today ensures that our valued customers have different product options for virtually every thermal transfer application. Using Toshiba ribbons ensures optimum print quality causing minimum wear on working parts - in particular to the printhead.

Before a ribbon is certified by Toshiba it must first undergo stringent tests to ensure its continuity and reliability in the field. It is assessed on a variety of receiving materials, and at every speed and temperature combination. Only once this procedure is complete and deemed successful will the ribbon receive its certificate of approval.

Other Approved Ribbon Type Available						
Standard applications	Wax	Wax/resin				
	Super wax/ resin	Full resin				
Specialist resins for	Wash-care & textile labelling	Harsh chemical and industrial uses				
	Extreme automotive and aviation environments					

The Complete Toshiba Ribbon Range

Quality codes	AW1F	AW5	AW6F	AW7F	AG2	AG3	AG4 AG4F	AG6E		AS2 AS2F	AS3 AS3F
* Available in colour	*			SolFree	*	*	*		*		
RIBBON TYPE											
General purpose wax	•	•	•	•							
General purpose wax/resin smearless					•	•		•			
Scratch/solvent resistant resin									•		
Economy resin/ enhanced wax/resin							•				
Specialist super resin										•	
Washcare textile resin											•
PRINTER TYPE											
B-443, B-452, B-852, B-SV4T, & B-SA4T flat head printer	•	•	•	•		•	•		•	•	•
BX and SX near edge printer					•		•	•	•	•	•
CB-416 and CB-426 colour printer					•				•	•	•
B-EV4 flat head printer	•	•	•	•		•	•		•		
SX-600 flat head printer									•		
B-EX Type 1 near edge printer					•		•	•	•	•	•
B-EX Type 2 and 3 flat head printer	•	•	•	•		•	•		•	•	•

TOSHIBA - leading the way through quality and innovation.

All Toshiba's range of consumable products meet the current EU Directives for Health and Safety; ROHS; REACH; Banned Substances and Waste and Packaging.



Henry Ho

Product Manager - Thermal Ribbons Email: Henry.Ho@toshibatec.ca Phone: 905 470-3500 Ext. 2168



B-SA4

Networking Pow

Comes Standar

^{*} Please note that not using TOSHIBA approved ribbons affects any printer and printhead warranties offered by TOSHIBA. All company and/or product names are trademarks and/or registered trademarks of their respective owners. All features and specifications are subject to change without notice.