

TOSHIBA

e-STUDIO™ 2010AC

- > Colour Multifunction Printer
- > 20 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready



**TOGETHER
INFORMATION**

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/LED Printing/ Heat Roller Fusing
Display	10.1" Colour WSVGA Touch Screen Tilting Display
Copy Speed	20 PPM (LT)
First Copy Out	Colour: 9.5 seconds Monochrome: 7.1 seconds
Warm-Up Time	Approx. 21 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	ST-R to LD, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 350 Sheets/Max. 2,900 Sheets
Original Feed	Optional 100-Sheet RADF
Scan Speed & Weights	RADF Scan: Up to 73 IPM (Monochrome or Colour), Simplex: 9.3-41.8 lb Bond, Duplex: 13.3-41.8 lb Bond
Max. Original Size	Ledger
Paper Feed Sizes	Drawer 1: 250 Sheets-ST-R to LD Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to LD Opt. Paper Feed Unit: 550 Sheets-ST-R to LD Opt. 550-Sheet Paper Feed Pedestal-ST-R to LD Opt. 550-Sheet Drawer for PFP -ST-R to LD Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 250 Sheets-16 lb Bond-90 lb Index Stack Feed Bypass: 100 Sheets-16 lb Bond-110 lb Index Opt. Paper Feed Unit: 550 Sheets-16 lb Bond-90 lb Index Opt. 550-Sheet Paper Feed Pedestal: 16 lb Bond-90 lb Index Opt. 550-Sheet Drawer for PFP: 16 lb Bond-90 lb Index Opt. Envelope Cassette for PFP: 16 lb Bond-90 lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type): 17-28 lb Bond
Paper Weights	Standard Automatic Duplex Unit: 16 lb Bond-90 lb Index
Duplex	Standard Automatic Duplex Unit: 16 lb Bond-90 lb Index
Reproduction Ratio	25% to 400%
Max Duty Cycle	Max. 67.2K Month
Weight	Approx. 126 lb
Approx. Dimensions	22.6" (W) x 23" (D) x 31" (H)
CMYK Toner Yield	CMY: 33.6K, BK: 38.4K @ 5%
Power Source	120 Volts, 50/60 Hz, 12 Amps
Power Consumption	Maximum 1.5kW (120V)
CPU	Intel Atom™ 1.33GHz (Dual-Core)
Memory	2GB, Max. 4GB
Hard Disk Drive	320GB Self-Encrypting Drive

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	20/Pages Per Minute (LT)
Print Resolution	600 x 600 dpi (5 bit) 600 x 1,200 dpi (1 bit) PS3 Only
Operating Systems	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7, 8.1, 10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh® Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or EtherTalk, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Print Drivers	Windows Server® 2008 SP2 (32-bit, 64-bit) Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016, Windows® 10 (32-bit, 64-bit), macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed), Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess
Account Control	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for firmware update, Integrity Check function, Image Log, Card Authentication, NFC Authentication
*Conformance with HCD-PPv1.0 in High security mode.

Environmental Stds. Certification

ENERGY STAR® (V2.0), EPEAT Gold
WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Scan Specifications

Scan Speed	RADF Scan: Up to 73 IPM (Monochrome or Colour)
Scan Modes	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Colour/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations /Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Colour Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options	Card Reader Holder	GR-1320
RADF	4GB Memory Option	GC-1410
Platen Cover	FIPS HDD	GE-1230
	Meta Scan Enabler	GS-1010
	IPsec Enabler	GP-1080
Additional Paper Options	Unicode Font Enabler	GS-1007
Paper Feed Pedestal	Embedded OCR Enabler	GS-1080
Paper Feed Unit	Multi-Station Print Enabler	GS-1090
Drawer Module	USB Hub Option	GR-1310
Envelope Cassette Option	External Interface Enabler	GS-1020
Large Capacity Feeder	Monotype Font Option	GB-2050L
Finishing Options		
Inner Finisher	MJ-1042-B	
Saddle-Stitch Finisher	MJ-1110-B	
Hole Punch Unit (MJ-1042-B)	MJ-6011N	ST-5005
Hole Punch Unit (MJ-1110-B)	MJ-6105N	KK-2560
Bridge Kit (MJ-1110-B)	KN-5005	Harness Kit for Coin Controller
Job Separator	MJ-5014	GQ-1280
		Hardcopy Security
		GP-1190A
Connectivity/Security Options		
FAX Unit/2nd Line for FAX Unit	GD-1370A-N	
Wireless LAN/Bluetooth	GN-4020	
Bluetooth Keyboard	GR-9000	
Accessory Tray	GR-1330	
Panel 10-Key Option	GR-1340	
		e-BRIDGE Plus Apps
		Office365
		GB-365Node
		Includes:
		OneDrive® 365 App
		SharePoint® 365 App
		Exchange 365 App

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership or Toshiba Tec Canada Business Solutions Inc. Branch for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

75 Tiverton Court
Markham, Ontario
L3R 4M8

Phone
Fax

905-470-3500
905-470-3450

Web Site

www.toshiba.ca

