

# TOSHIBA

## e-STUDIO4518A series

- > Black & White Multifunction Printer
- > Up to 45 PPM
- > Medium/Large Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready



**TOGETHER**  
INFORMATION

# e-STUDIO™ 2518A/3018A/3518A/4518A

## Main Specifications

<b>Copy System</b>	Indirect Electrostatic Photographic Method/OPC/Laser Printing/ Heat Roller Fusing
<b>Display</b>	10.1" Colour WSVGA Touch Screen Tilting Display
<b>Copy Speed</b>	25/30/35/45 PPM (LT)
<b>First Copy Out</b>	4.3/4.3/3.6/3.6 Seconds
<b>Warm-Up Time</b>	Approx. 20 Seconds
<b>Copy Resolution</b>	2,400 x 600 dpi with Smoothing
<b>Stack Feed Bypass</b>	3.9" x 5.8" to LD, Envelope
<b>Multiple Copying</b>	Up to 999 Copies
<b>Paper Capacity</b>	Standard 1,200 Sheets/Max. 3,200 Sheets
<b>Original Feed</b>	Optional 300-Sheet DSDf or 100-Sheet RADf
<b>Scan Speed &amp; Weights</b>	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour), Simplex: 9.3-110 lb Bond, Duplex: 9.3-110 lb Bond RADf Scan: Up to 73 IPM (Monochrome or Colour): Simplex: 9.3-41.8 lb Bond, Duplex: 13.3-41.8 lb Bond
<b>Max. Original Size</b>	Ledger
<b>Paper Feed Sizes</b>	Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 550 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 100 Sheets-14 lb Bond-140 lb Index Opt. 550-Sheet Paper Feed Pedestal-16 lb Bond-140 lb Index Opt. 550-Sheet Drawer for PFP -16 lb Bond-140 lb Index Opt. Envelope Cassette for PFP-16 lb Bond-140 lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type), 17-28 lb Bond Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
<b>Paper Weights</b>	
<b>Duplex</b>	Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
<b>Reproduction Ratio</b>	25% to 400%
<b>Max Duty Cycle</b>	Max. 100K/120K/125K/150K Month
<b>Weight</b>	Approx. 125.2 lb
<b>Approx. Dimensions</b>	23" (W) x 23" (D) x 31" (H)
<b>Toner Yield</b>	43.9K @ 5%
<b>Power Source</b>	120 Volts, 50/60 Hz, 12 Amps
<b>Power Consumption</b>	Maximum 1.5kW (120V)
<b>CPU</b>	Intel Atom™ 1.33GHz (Dual-Core)
<b>Memory</b>	e-STUDIO2518A/3018A: 2GB, Max 4GB e-STUDIO3518A/4518A: 4GB
<b>Hard Disk Drive</b>	320GB Self-Encrypting Drive FIPS 140-2 Validated (Opt.)

## e-BRIDGE Next Print Specifications

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Speed</b>	25/30/35/45 Pages Per Minute (LT)
<b>Print Resolution</b>	600 x 600 dpi (1 bit) or 2,400 (Equivalence) x 600 dpi (with Smoothing) (ALL PDL), 1,200 x 1,200 dpi (2 bit) or 3,600 x 1,200 dpi (with Smoothing) PS3 Only
<b>Operating Systems</b>	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7, 8.1, 10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (macOS x 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13), Unix®, Linux®
<b>Network Protocols</b>	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh® Environments
<b>Printing Protocols</b>	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or EtherTalk, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
<b>Print Drivers</b>	Windows Server® 2008 SP2 (32-bit, 64-bit) Windows Server® 2008 R2 SP1 (64-bit), Windows Server® 2016, Windows® 7 SP1 (32-bit, 64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows® 10 (32-bit, 64-bit), macOS x 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
<b>Interface</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed), Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth
<b>Wireless Device</b>	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
<b>Device Management</b>	TopAccess
<b>Account Control</b>	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® domain) or Login Name/ Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
<b>Accessibility Features</b>	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



<b>Security Features</b>	User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/ IEC15408)*, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for firmware update, Integrity Check function, Image Log, Card Authentication, NFC Authentication *Conformance with HCD-PPv1.0 in High security mode. ENERGY STAR® (V2.0), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint® and Mopria®
<b>Environmental Stds. Certification</b>	

## Scan Specifications

<b>Scan Speed</b>	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour) RADf Scan: Up to 73 IPM (Monochrome or Colour)
<b>Scan Modes</b>	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
<b>Scan Resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>File Formats</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
<b>Image Compression</b>	Colour/Grayscale: JPEG (High, Middle, Low)

## Facsimile Specifications

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations /Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 IPM

## e-Filing Specifications

<b>Operation Method</b>	Colour Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## Accessories (Options)

<b>Platen &amp; Document Feeder Options</b>			
DSDf	MR-4000-B	Panel 10-Key Option	GR-1340
RADf	MR-3031-B	Card Reader Holder	GR-1320
Platen Cover	KA-5005PC	4GB Memory Option (eS2518/3018)	GC-1410
		FIPS HDD	GE-1230
		USB Hub	GR-1310
<b>Additional Paper Options</b>		Meta Scan Enabler	GS-1010
Paper Feed Pedestal	KD-1058-B	IPsec Enabler	GP-1080
Drawer Module	MY-1048-B	Unicode Font Enabler	GS-1007
Envelope Cassette Option	MY-1049-B	Embedded OCR Enabler	GS-1080
Large Capacity Feeder	KD-1059LT-B	Multi-Station Print Enabler	GS-1090
		Monotype Font Option	GB-2050L
<b>Finishing Options</b>		<b>Miscellaneous Options</b>	
Inner Finisher	MJ-1042-B	Stand	ST-5005
50-Sheets Staple Finisher	MJ-1109-B	Accessible Arm	KK-2560
Saddle-Stitch Finisher	MJ-1110-B	Harness Kit for Coin Controller	QQ-1280
Hole Punch Unit (MJ-1042-B)	MJ-6011N	Hardcopy Security Printing	GP-1190A
Hole Punch Unit (MJ-1109-B/1110-B)	MJ-6105N		
Bridge Kit (MJ-1109-B/1110-B)	KN-5005	<b>e-BRIDGE Plus Apps</b>	
Job Separator		Office365	GB-365Node
eS2518A/3018A	MJ-5014	Includes:	
eS3518A/4518A	MJ-5015	OneDrive® 365 App	
<b>Connectivity/Security Options</b>		SharePoint® 365 App	
FAX Unit/2nd Line for FAX Unit	GD-1370NA-N	Exchange 365 App	
Wireless LAN/Bluetooth	GN-4020		
Bluetooth Keyboard	GR-9000		
Accessory Tray	GR-1330		

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership or Toshiba Tec Canada Business Solutions Inc. Branch for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

### Corporate Office

75 Tiverton Court  
Markham, Ontario  
L3R 4M8

Phone  
Fax

905-470-3500  
905-470-3450

Web Site

www.toshiba.ca

