# **TOSHIBA**

# E-STUDIO478s

- > Black & White Multifunction Printer
- > 50 PPM
- Letter / Legal Size
- Reliable system that covers nearly all areas of your office document handling – offering print, scan, copy and fax functions.
- The e-STUDIO478s offer flexibility at your fingertips, thanks to mobile printing accessibility.
- A maximum paper capacity of up to 2,300 sheets guarantees a smooth output of even large print jobs.
- Intuitively access functions, apps and solutions via the 7" tiltable, colour touch panel.





#### Main Specifications

Display

Copy System Indirect Electrostatic Photographic Method/OPC/Laser

Printing/ Heat Roller Fusing

7" Color TFT Touch Screen Tilting Display

Copy Speed 50 PPM (LT)

First Copy Out As Fast as 6 Seconds Warm-Up Time Approx. 20 Seconds Copy Resolution Up to 600 x 600 dpi 3.0" x 5.0" to LG, Envelope Multipurpose Tray **Multiple Copying** Up to 999 Copies

Standard 650 Sheets/Max. 2,300 Sheets Paper Capacity

Original Feed Standard 100-Sheet DSDF

Scan Speed DSDF Scan: Mono - Up to 100 IPM Duplex, 50 IPM Simplex

Colour - Up to 64 IPM Duplex, 32 IPM Simplex,

14-32 lb Bond Max. Original Size LG (Legal)

Drawer 1: 550 Sheets - 4.13" x 5.83" to LG Paper Feed Sizes

Multipurpose Tray: 100 Sheets - 3.0" x 5.0" to LG Opt. Drawers: 550 Sheets - 4.13" x 5.83" to LG

**Paper Weights** Drawers: 16lb - 32 lb Bond

Multipurpose Tray: 16-58 lb Bond Standard Automatic Duplex Unit: 16 – 24 lb Bond Duplex

Reproduction Ratio 25% to 400% Max Duty Cycle Max. 157K Month Weight

Approx. 49.2 lb 19.3" (W) x 18.8" (D) x 21.5" (H) Approx. Dimensions

Toner Yield 20K @ 5%

120 Volts, 50/60 Hz, 15 Amps **Power Source Power Consumption** Maximum 1.5kW (120V) CPU 1.2GHz (Quad-Core)

Hard Disk Drive 320GB

# **Print Specifications**

PostScript 3, PCL 6, PCL 5, PPDS, PDF v1.7, XPS, HTML,

Direct Image, MS Office 50 Pages Per Minute (LT) Print Speed

**Print Resolution** 1200 x 1200 dpi, 2400 Image Quality, 1200 Image Quality

600 x 600 dpi, 300 x 300 dpi Standard Ports

Rear USB 2.0 Specification High Speed Certified Port (Type A), Front USB

2.0 Specification High Speed Certified Port (Type A), Gigabit Ethernet (10/100/1000), USB 2.0 Specification High Speed Certified Port (Type B), One

Internal Card Slot

WiFi Option/Internal 1284-B Bidirectional Parallel, Ontional Network

Internal RS-232C Serial **Ports Device Management** Embedded Web Server

Accessibility Features Tilt Front Panel, 508 Accessibility Support, Voice Guidance Security Features

Role Based Access Controls, Ease of Use for User Access Control, Breach Mitigation, Moving Processes Off of Root (Emulators, Network, Security), Secure Element SmartCard, Protect Encryption Keys for Hard Disk, Protect Device Certificates, Provide True Random Number Generation to Meet Next-Gen FIPS and CC Requirements, Customer-Installable, Option, Unified Integrated Address Book, Common Admin Management for Internal &

eSF App Contacts, Configuration via EWS, Supports Device Quotas App, Common Criteria Certification, PKI/SCAC Support, Setup Local Accounts on

Operator Panel

Environmental Sleep & Hibernate Modes, Eco Mode, Quiet Mode, Blue Angel/RAL-UZ-122 Certification, RoHS Compliant Energy Star Certified, EPEAT Silver, Mercury **Features** 

Free, Support for Recycled Paper

Certifications WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP

## Scan Specifications

Scan Speed DSDF Scan: Mono - Up to 100 IPM Duplex, 50 IPM

Simplex Colour - Up to 64 IPM Duplex, 32 IPM Simplex USB Thumbdrive, E-Mail, FTP, Network or USB Connected Scan Destinations

Computer, Windows Network Folder

Scan Resolution 600 dpi (Max) TIFF, JPG (JPEG), PDF (Regular, Secure, Archival (PDF/A), **File Formats** 

Searchable), XPS

PDF 1 bit: CCITT G4, ZLIB (Flate), 8/24 bit: ZLIB (Flate), JPEG, MRC (Mixed **Image Compression** 

Raster Content), TIFF 1 bit: CCITT G4, 8/24 bit – Packbits, LZW, JPEG, JPG 8/24 bit: JPEG, XPS 1bit: ZLIB (Flate), 8/24 bit - JPEG, ZLIB (Flate)

### **Facsimile Specifications**

Compatibility Transmission Speed Super G3

Approx. 3 Seconds Per Page

Fax Modem Speed Up to 33.6 Kbps Fax Shortcuts

500 - Based on an Average Shortcut 25 Characters for Name, 10 Characters for Number and 4 Characters for Shortcut Id. Maximum Characters - 512 and

Each Location Separated by a Semi Colon. 46 Locations Using a 10-Digit

Phone Number, 64 Locations Using a 7-Digit Phone Number **Group Fax** 400 Locations - Each Number in a Fax Shortcut is a Location

# Accessories (Options)

550 Sheet Paper Cassette KD-1061 Inline Stapler MJ-1044 Wireless LAN Adapter GN-1170 Forms and Barcode Card GB-2080I XK IPDS Card GB-2100LXK Adjustable Printer Stand ST-LEXA4

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/)













Designs and specifications subject to change without notice. Specifications may vary by conditions Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership or Toshiba Tec Canada Business Solutions Inc. Branch for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or

**Corporate Office** 

75 Tiverton Court Markham, Ontario L3R 4M8

Phone

905-470-3500 905-470-3450

Web Site

www.toshiba.ca